

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : ARALDITE® RAPID HARDENER

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Adhesives

#### 1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA  
Address : Everslaan 45  
3078 Everberg  
Belgium  
Telephone : +41 61 299 20 41  
Telefax : +41 61 299 20 40

E-mail address of person responsible for the SDS : Global\_Product\_EHS\_AdMat@huntsman.com

#### 1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234  
France ORFILA: +33(0)145425959  
ASIA: +65 6336-6011  
China: +86 20 39377888  
+86 532 83889090  
India: + 91 22 42 87 5333  
Australia: 1800 786 152  
New Zealand: 0800 767 437  
USA: +1/800/424.9300

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word : Danger

Hazard statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ eye protection/ face protection.

**Response:**  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

Hazardous components which must be listed on the label:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine

2,4,6-Tris(dimethylaminomethyl)phenol

N,N,4-trimethylpiperazine-1-ethylamine

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No. EC-No. Index-No.	Classification	Concentration (% w/w)

## ARALDITE® RAPID HARDENER

Version 1.0      Revision Date: 09.10.2018      SDS Number: 400001007755      Date of last issue: -  
Date of first issue: 09.10.2018

	Registration number		
2,2'-[1,2-Ethanediy]bis(oxy)]bis(ethanethiol)	14970-87-7 239-044-2 -	Acute Tox. 4; H302 Acute Tox. 4; H332 Aquatic Chronic 2; H411	>= 2.5 - < 10
N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	10563-29-8 234-148-4 01-2119970376-29	Acute Tox. 4; H302 Skin Corr. 1A; H314 Skin Sens. 1B; H317	>= 1 - < 3
2,4,6-Tris(dimethylaminomethyl)phenol	90-72-2 202-013-9 603-069-00-0 01-2119560597-27	Skin Corr. 1C; H314 Eye Dam. 1; H318	>= 1 - < 3
N,N,4-trimethylpiperazine-1-ethylamine	104-19-8 203-183-7 -	Acute Tox. 4; H302 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 1 - < 2.5

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : No data is available on the product itself.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

See Section 1 for emergency contact information.  
For personal protection see section 8.  
For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Recommended storage temperature : 2 - 40 °C

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : No data available

## ARALDITE® RAPID HARDENER

Version 1.0      Revision Date: 09.10.2018      SDS Number: 400001007755      Date of last issue: -  
Date of first issue: 09.10.2018

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m <sup>3</sup>	GB EH40
		STEL	200 ppm 966 mg/m <sup>3</sup>	GB EH40

##### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	Workers	Inhalation	Long-term systemic effects	3.7 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	7.5 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	3.7 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	7.5 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	0.67 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0.65 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	0.65 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	0.2 mg/kg

##### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,4,6-Tris(dimethylaminomethyl)phenol	Fresh water	0.084 mg/l
Remarks:	Assessment Factors	
	Marine water	0.0084 mg/l
	Assessment Factors	
	Sewage treatment plant	0.2 mg/l
	Assessment Factors	
N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	Fresh water	9.2 µg/l
	Assessment Factors	
	Marine water	0.92 µg/l
	Assessment Factors	

## ARALDITE® RAPID HARDENER

Version: 1.0      Revision Date: 09.10.2018      SDS Number: 400001007755      Date of last issue: -  
Date of first issue: 09.10.2018

	Freshwater - intermittent	92 µg/l
	Assessment Factors	
	Sewage treatment plant	18.1 mg/l
	Assessment Factors	
	Fresh water sediment	0.0336 mg/kg
	Equilibrium method	
	Marine sediment	0.00336 mg/kg
	Equilibrium method	
	Soil	0.00132 mg/kg
	Equilibrium method	

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection  
Material : butyl-rubber  
Break through time : > 8 h

Material : Solvent-resistant gloves (butyl-rubber)

Material : Nitrile rubber  
Break through time : 10 - 480 min

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapour type (A)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : liquid

## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

Colour	: light yellow
Odour	: slight
Odour Threshold	: No data is available on the product itself.
pH	: No data is available on the product itself.
Freezing point	: No data is available on the product itself.
Melting point	: No data is available on the product itself.
Boiling point	: > 200 °C
Flash point	: > 100 °C Method: Pensky-Martens closed cup, closed cup
Evaporation rate	: No data is available on the product itself.
Flammability (solid, gas)	: No data is available on the product itself.
Burning rate	: No data is available on the product itself.
Upper explosion limit / Upper flammability limit	: No data is available on the product itself.
Lower explosion limit / Lower flammability limit	: No data is available on the product itself.
Vapour pressure	: < 0.01 hPa (20 °C)
Relative vapour density	: No data is available on the product itself.
Relative density	: No data is available on the product itself.
Density	: 1.165 g/cm <sup>3</sup> (25 °C)
Solubility(ies)	
Water solubility	: practically insoluble (20 °C)
Solubility in other solvents	: No data is available on the product itself.
Partition coefficient: n-octanol/water	: No data is available on the product itself.
Auto-ignition temperature	: No data is available on the product itself.
Decomposition temperature	: > 200 °C
Viscosity	
Viscosity, dynamic	: 20,000 - 40,000 mPa.s (25 °C)
Explosive properties	: No data is available on the product itself.



## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

Oxidizing properties : No data is available on the product itself.

### 9.2 Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

### 10.4 Conditions to avoid

Conditions to avoid : None known.

### 10.5 Incompatible materials

Materials to avoid : None known.

### 10.6 Hazardous decomposition products

Nitrogen oxides (NO<sub>x</sub>)  
Burning produces noxious and toxic fumes.  
Carbon oxides

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Acute oral toxicity - Product : LD50 (Rat): 2,300 mg/kg

Acute inhalation toxicity - Product : Acute toxicity estimate : > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity - Product : Acute toxicity estimate : > 2,000 mg/kg  
Method: Calculation method

Acute toxicity (other routes of administration) : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

### Skin corrosion/irritation

#### Product:

Species: Rabbit  
Assessment: Irritant  
Result: Irritating to skin.

### Serious eye damage/eye irritation

#### Components:

2,2'-[1,2-Ethanediy]bis(oxy)]bis(ethanethiol):

Species: Bovine cornea  
Method: OECD Test Guideline 437  
Result: No eye irritation

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Assessment: Severe eye irritation  
Result: Corrosive

2,4,6-Tris(dimethylaminomethyl)phenol:

Species: Rabbit  
Assessment: Corrosive  
Result: Corrosive

N,N,4-trimethylpiperazine-1-ethylamine:

Result: Risk of serious damage to eyes.

### Respiratory or skin sensitisation

#### Components:

2,2'-[1,2-Ethanediy]bis(oxy)]bis(ethanethiol):

Test Type: Maximisation Test  
Exposure routes: Skin  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: Does not cause skin sensitisation.

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Exposure routes: Skin  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: The product is a skin sensitizer, sub-category 1B.

2,4,6-Tris(dimethylaminomethyl)phenol:

Exposure routes: Skin  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: Does not cause skin sensitisation.

N,N,4-trimethylpiperazine-1-ethylamine:

Result: May cause sensitisation by skin contact.

Assessment: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

### Germ cell mutagenicity

#### Components:

2,2'-[1,2-Ethanediy]bis(oxy)]bis(ethanethiol):

Genotoxicity in vitro

- : Test Type: Ames test  
Test system: Salmonella tryphimurium and E. coli  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: negative  
GLP: yes
- : Test Type: gene mutation test  
Test system: mouse lymphoma cells  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 490  
Result: negative
- : Test system: Human lymphocytes  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 487  
Result: negative

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Genotoxicity in vitro

- : Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 487  
Result: negative
- : Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: negative
- : Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: negative

2,4,6-Tris(dimethylaminomethyl)phenol:

Genotoxicity in vitro

- : Concentration: 5000 ug/plate  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: negative
- : Concentration: 2500 ug/plate  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 473  
Result: negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

: Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : No data available

### Carcinogenicity

#### Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Species: Mouse, male

Application Route: Dermal

Exposure time: 20 month(s)

Frequency of Treatment: 3 daily

Result: negative

Carcinogenicity - Assessment : No data available

### Reproductive toxicity

#### Components:

2,2'-[1,2-Ethanedithylbis(oxy)]bis(ethanethiol):

Effects on fertility : Species: Rat, male and female

Dose: 50, 100, 150 mg/kg

General Toxicity - Parent: No observed adverse effect level:  
50 mg/kg body weight

General Toxicity F1: No observed adverse effect level: 50  
mg/kg body weight

Method: OECD Test Guideline 421

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Species: Rat, male and female

Application Route: Oral

Method: OECD Test Guideline 422

Result: Animal testing did not show any effects on fertility.

2,4,6-Tris(dimethylaminomethyl)phenol:

Species: Rat, male and female

Application Route: Oral

Method: OECD Test Guideline 422

Remarks: No significant adverse effects were reported

#### Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Effects on foetal development : Species: Rat, male and female

Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:  
15 mg/kg body weight

Developmental Toxicity: No observed adverse effect level: 15

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

mg/kg body weight  
Embryo-foetal toxicity: No observed adverse effect level: 15  
mg/kg body weight  
Method: OECD Test Guideline 422  
Result: No effects on fertility and early embryonic  
development were detected.

### Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:  
Reproductive toxicity - : No evidence of adverse effects on sexual function and fertility,  
Assessment or on development, based on animal experiments.

### **STOT - single exposure**

No data available

### **STOT - repeated exposure**

No data available

### **Repeated dose toxicity**

#### Components:

2,2'-[1,2-Ethanedylbis(oxy)]bis(ethanethiol):

Species: Rat, male and female

NOAEL: 60 mg/kg

Application Route: Oral

Dose: 20, 60, 180 mg/kg

Method: OECD Test Guideline 407

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Species: Rat, male and female

NOEC: 550

Application Route: Ingestion

Test atmosphere: vapour

Exposure time: 3 Weeks Number of exposures: 7 d

Method: Subchronic toxicity

Species: Mouse, male

NOAEL:  $\geq 56.3$

Application Route: Skin contact

Exposure time: 20 h Number of exposures: 3 d

Method: Chronic toxicity

2,4,6-Tris(dimethylaminomethyl)phenol:

Species: Rat, male and female

NOEL: 15 mg/kg

Application Route: Ingestion

Exposure time: 1,032 h Number of exposures: 7 d

Method: Subacute toxicity

Repeated dose toxicity - : No data available  
Assessment

## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

### Aspiration toxicity

No data available

### Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

### Toxicology, Metabolism, Distribution

No data available

### Neurological effects

No data available

### Further information

#### Product:

Remarks: No data available

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

2,2'-[1,2-Ethanediy]bis(oxy)]bis(ethanethiol):

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 5.7 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 0.76 mg/l  
aquatic invertebrates  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202

## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 3.11 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

Ecotoxicology Assessment  
Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 9.2 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 202

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 21 mg/l  
Exposure time: 72 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Pseudomonas putida): 181 mg/l  
Exposure time: 16 h  
Test Type: static test  
Test substance: Fresh water  
Method: DIN 38 412 Part 8

2,4,6-Tris(dimethylaminomethyl)phenol:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 175 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates : LC50 : 718 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: Marine water

Toxicity to algae : ErC50 (Desmodesmus subspicatus (green algae)): 84 mg/l  
Exposure time: 72 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 201

## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

NOEC (Desmodesmus subspicatus (green algae)): 6.25 mg/l  
Exposure time: 72 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 201

Ecotoxicology Assessment  
Chronic aquatic toxicity : This product has no known ecotoxicological effects.

N,N,4-trimethylpiperazine-1-ethylamine:  
Ecotoxicology Assessment  
Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

#### Components:

2,2'-[1,2-Ethanedithylbis(oxy)]bis(ethanethiol):

Biodegradability : Test Type: aerobic  
Inoculum: activated sludge  
Concentration: 38.2 mg/l  
Result: Not biodegradable  
Biodegradation: < 10 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301A

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 28 d  
Method: ISO

2,4,6-Tris(dimethylaminomethyl)phenol:

Biodegradability : Inoculum: activated sludge  
Concentration: 2 mg/l  
Result: Not biodegradable  
Biodegradation: 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

### 12.3 Bioaccumulative potential

#### Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Partition coefficient: n-octanol/water : log Pow: 0.5

log Pow: -0.56 (25 °C)  
pH: 11.6  
Method: OECD Test Guideline 107

2,4,6-Tris(dimethylaminomethyl)phenol:

Partition coefficient: n-octanol/water : log Pow: 0.219 (21.5 °C)  
Method: OPPTS 830.7550



## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

No data available

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

## SECTION 14: Transport information

**IATA**

14.1 UN number	: UN 1760
14.2 UN proper shipping name	: Corrosive liquid, n.o.s. (DIMETHYL DIPROPYL TRIAMINE, 1-(DIMETHYLAMINOETHYL)-4-METHYLPIPERAZINE)
14.3 Transport hazard class(es)	: 8
14.4 Packing group	: III
Labels	: Corrosive
Packing instruction (cargo aircraft)	: 856
Packing instruction (passenger aircraft)	: 852

**IMDG**

14.1 UN number	: UN 1760
14.2 UN proper shipping name	: CORROSIVE LIQUID, N.O.S.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

(DIMETHYL DIPROPYL TRIAMINE, 1-(DIMETHYLAMINOETHYL)-4-METHYLPIPERAZINE)

**14.3 Transport hazard class(es)** : 8

**14.4 Packing group** : III

Labels : 8

EmS Code : F-A, S-B

**14.5 Environmental hazards**

Marine pollutant : no

### ADR

**14.1 UN number** : UN 1760

**14.2 UN proper shipping name** : CORROSIVE LIQUID, N.O.S.

(DIMETHYL DIPROPYL TRIAMINE, 1-(DIMETHYLAMINOETHYL)-4-METHYLPIPERAZINE)

**14.3 Transport hazard class(es)** : 8

**14.4 Packing group** : III

Labels : 8

**14.5 Environmental hazards**

Environmentally hazardous : no

### RID

**14.1 UN number** : UN 1760

**14.2 UN proper shipping name** : CORROSIVE LIQUID, N.O.S.

(DIMETHYL DIPROPYL TRIAMINE, 1-(DIMETHYLAMINOETHYL)-4-METHYLPIPERAZINE)

**14.3 Transport hazard class(es)** : 8

**14.4 Packing group** : III

Labels : 8

**14.5 Environmental hazards**

Environmentally hazardous : no

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
REACH - List of substances subject to authorisation - Future sunset date	: Not applicable

## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

**The components of this product are reported in the following inventories:**

DSL	: This product contains one or several components that are not on the Canadian DSL nor NDSL.
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: On the inventory, or in compliance with the inventory

**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOIC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

**Full text of H-Statements**

H302	: Harmful if swallowed.
H311	: Toxic in contact with skin.
H314	: Causes severe skin burns and eye damage.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.

## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

H332	: Harmful if inhaled.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Skin Corr.	: Skin corrosion
Skin Sens.	: Skin sensitisation
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

### Further information

#### Classification of the mixture:

Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 3	H412

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® RAPID HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09.10.2018	400001007755	Date of first issue: 09.10.2018

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : ARALDITE® RAPID RESIN

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Adhesives

#### 1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA  
Address : Everslaan 45  
3078 Everberg  
Belgium  
Telephone : +41 61 299 20 41  
Telefax : +41 61 299 20 40

E-mail address of person responsible for the SDS : Global\_Product\_EHS\_AdMat@huntsman.com

#### 1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234  
France ORFILA: +33(0)145425959  
ASIA: +65 6336-6011  
China: +86 20 39377888  
+86 532 83889090  
India: + 91 22 42 87 5333  
Australia: 1800 786 152  
New Zealand: 0800 767 437  
USA: +1/800/424.9300

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H318	Causes serious eye damage.
	H411	Toxic to aquatic life with long lasting effects.

Precautionary statements	<b>Prevention:</b>	
	P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
	P264	Wash skin thoroughly after handling.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/ eye protection/ face protection.

#### Response:

P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P391	Collect spillage.

Hazardous components which must be listed on the label:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

1,4-bis(2,3-epoxypropoxy)butane

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3 216-823-5 603-073-00-2	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 70 - < 90

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

	01-2119456619-26	Aquatic Chronic 2; H411	
1,4-Bis(2,3-epoxypropoxy)butane	2425-79-8 219-371-7 603-072-00-7 01-2119494060-45	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 3 - < 10

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Treat symptomatically.  
Get medical attention if symptoms occur.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

#### 4.2 Most important symptoms and effects, both acute and delayed

None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.



## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides  
Halogenated compounds

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : No data is available on the product itself.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Refer to protective measures listed in sections 7 and 8.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

### 6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information.,  
For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling	: Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Advice on protection against fire and explosion	: Normal measures for preventive fire protection.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers.
Advice on common storage	: For incompatible materials please refer to Section 10 of this SDS.
Further information on storage stability	: Stable under normal conditions.
Recommended storage temperature	: 2 - 40 °C

### 7.3 Specific end use(s)

Specific use(s)	: No data available
-----------------	---------------------

## ARALDITE® RAPID RESIN

Version: 1.0      Revision Date: 10.10.2018      SDS Number: 400001008131      Date of last issue: -  
Date of first issue: 10.10.2018

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Workers	Dermal	Systemic effects, Short-term exposure	8.33 mg/kg bw/day
	Workers	Inhalation	Systemic effects, Short-term exposure	12.25 mg/m3
	Workers	Dermal	Systemic effects, Long-term exposure	8.33 mg/kg bw/day
	Workers	Inhalation	Systemic effects, Long-term exposure	12.25 mg/m3
	Consumers	Dermal	Systemic effects, Short-term exposure	3.571 mg/kg bw/day
	Consumers	Oral	Systemic effects, Short-term exposure	0.75 mg/kg bw/day
	Consumers	Dermal	Systemic effects, Long-term exposure	3.571 mg/kg bw/day
	Consumers	Oral	Systemic effects, Long-term exposure	0.75 mg/kg bw/day

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Fresh water	0.006 mg/l
Remarks:	Assessment Factors	
	Marine water	0.0006 mg/l
	Assessment Factors	
	Freshwater - intermittent	0.018 mg/l
	Assessment Factors	
	Fresh water sediment	0.996 mg/kg
	Equilibrium method	
	Marine sediment	0.0996 mg/kg
	Equilibrium method	
	Soil	0.196 mg/kg

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

	Equilibrium method	
	Sewage treatment plant	10 mg/l
	Assessment Factors	
	Secondary Poisoning	11 mg/kg

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

#### Hand protection

Material : butyl-rubber  
Break through time : > 8 h

Material : Solvent-resistant gloves (butyl-rubber)

Material : Nitrile rubber  
Break through time : 10 - 480 min

Material : Neoprene gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Filter type : Combined particulates and organic vapour type (A-P)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : light yellow

Odour : slight

Odour Threshold : No data is available on the product itself.

pH : 6 (20 °C)  
Concentration: 500 g/l

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

Freezing point	: No data is available on the product itself.
Melting point	: No data is available on the product itself.
Boiling point	: > 200 °C
Flash point	: > 200 °C Method: Pensky-Martens closed cup, closed cup
Evaporation rate	: No data is available on the product itself.
Flammability (solid, gas)	: No data is available on the product itself.
Burning rate	: No data is available on the product itself.
Upper explosion limit / Upper flammability limit	: No data is available on the product itself.
Lower explosion limit / Lower flammability limit	: No data is available on the product itself.
Vapour pressure	: < 0.002 hPa (20 °C)
Relative vapour density	: No data is available on the product itself.
Relative density	: No data is available on the product itself.
Density	: 1.17 g/cm <sup>3</sup> (25 °C)
Solubility(ies) Water solubility	: practically insoluble (20 °C)
Solubility in other solvents	: No data is available on the product itself.
Partition coefficient: n-octanol/water	: No data is available on the product itself.
Auto-ignition temperature	: No data is available on the product itself.
Decomposition temperature	: > 200 °C
Viscosity Viscosity, dynamic	: 25,000 - 45,000 mPa.s (25 °C)
Explosive properties	: No data is available on the product itself.
Oxidizing properties	: No data is available on the product itself.

### 9.2 Other information

No data available

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

#### 10.4 Conditions to avoid

Conditions to avoid : None known.

#### 10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases  
Strong oxidizing agents

#### 10.6 Hazardous decomposition products

Carbon oxides

Burning produces noxious and toxic fumes.

No hazardous decomposition products are known.

Hazardous decomposition products : carbon dioxide  
carbon monoxide  
Halogenated compounds

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Acute oral toxicity - Product : Acute toxicity estimate : > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity - Product : Acute toxicity estimate : > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity - Product : Acute toxicity estimate : > 2,000 mg/kg  
Method: Calculation method

Acute toxicity (other routes of administration) : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

### Skin corrosion/irritation

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Assessment: Mild skin irritant

Method: OECD Test Guideline 404

Result: Irritating to skin.

1,4-bis(2,3-epoxypropoxy)butane:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Skin irritation

### Serious eye damage/eye irritation

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Assessment: Mild eye irritant

Method: OECD Test Guideline 405

Result: Irritating to eyes.

1,4-bis(2,3-epoxypropoxy)butane:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Risk of serious damage to eyes.

### Respiratory or skin sensitisation

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Exposure routes: Skin

Species: Mouse

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 429

Result: Causes sensitisation.

1,4-bis(2,3-epoxypropoxy)butane:

Exposure routes: Skin

Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

Assessment: No data available

### Germ cell mutagenicity

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

Result: positive

: Concentration: 0 - 5000 ug/plate  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: positive

1,4-bis(2,3-epoxypropoxy)butane:

Genotoxicity in vitro : Concentration: 10 - 5000 ug/plate  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: positive  
Remarks: Not classified due to data which are conclusive although insufficient for classification.

: Concentration: 1 - 100 µg/L  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 473  
Result: positive  
Remarks: Not classified due to data which are conclusive although insufficient for classification.

### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vivo : Cell type: Germ  
Application Route: Oral  
Method: OECD Test Guideline 478  
Result: negative

Cell type: Somatic  
Application Route: Oral  
Dose: 0 - 5000 mg/kg  
Method: OPPTS 870.5395  
Result: negative

1,4-bis(2,3-epoxypropoxy)butane:

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Test species: Mouse  
Cell type: Somatic  
Application Route: Oral  
Exposure time: 4 d  
Dose: 187.5 - 750 mg/kg  
Method: OECD Test Guideline 474  
Result: negative

Test Type: unscheduled DNA synthesis assay



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

Test species: Rat  
Cell type: Liver cells  
Application Route: Oral  
Method: OECD Test Guideline 486  
Result: negative

### **Components:**

1,4-bis(2,3-epoxypropoxy)butane:

Germ cell mutagenicity- : Weight of evidence does not support classification as a germ  
Assessment cell mutagen.

Germ cell mutagenicity- : No data available  
Assessment

### **Carcinogenicity**

#### **Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

Application Route: Oral

Exposure time: 24 month(s)

Dose: 15 mg/kg

Frequency of Treatment: 7 days/week

Method: OECD Test Guideline 453

Result: negative

Species: Mouse, male

Application Route: Dermal

Exposure time: 24 month(s)

Dose: 0.1 mg/kg

Frequency of Treatment: 3 days/week

Method: OECD Test Guideline 453

Result: negative

Species: Rat, female

Application Route: Dermal

Exposure time: 24 month(s)

Dose: 1 mg/kg

Frequency of Treatment: 5 days/week

Method: OECD Test Guideline 453

Result: negative

Carcinogenicity - : No data available  
Assessment

### **Reproductive toxicity**

#### **Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

Application Route: Oral  
Dose: >750 milligram per kilogram  
General Toxicity - Parent: No-observed-effect level: 540 mg/kg body weight  
General Toxicity F1: No-observed-effect level: 540 mg/kg body weight  
Symptoms: No adverse effects  
Method: OECD Test Guideline 416  
Result: No effects on fertility and early embryonic development were detected.

### **Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on foetal development

: Species: Rabbit, female  
Application Route: Dermal  
General Toxicity Maternal: No observed adverse effect level: 30 mg/kg body weight  
Method: Other guidelines  
Result: No teratogenic effects

Species: Rabbit, female  
Application Route: Oral  
General Toxicity Maternal: No observed adverse effect level: 60 mg/kg body weight  
Method: OECD Test Guideline 414  
Result: No teratogenic effects

Species: Rat, female  
Application Route: Oral  
General Toxicity Maternal: No observed adverse effect level: 180 mg/kg body weight  
Method: OECD Test Guideline 414  
Result: No teratogenic effects

Reproductive toxicity - Assessment : No data available

### **STOT - single exposure**

No data available

### **STOT - repeated exposure**

No data available

### **Repeated dose toxicity**

#### **Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

NOAEL: 50 mg/kg

Application Route: Ingestion

Exposure time: 14 Weeks Number of exposures: 7 d

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

Method: Subchronic toxicity

Species: Rat, male and female

NOEL: 10 mg/kg

Application Route: Skin contact

Exposure time: 13 WeeksNumber of exposures: 5 d

Method: Subchronic toxicity

Species: Mouse, male

NOAEL: 100 mg/kg

Application Route: Skin contact

Exposure time: 13 WeeksNumber of exposures: 3 d

Method: Subchronic toxicity

1,4-bis(2,3-epoxypropoxy)butane:

Species: Rat, male and female

NOAEL: 200 mg/kg

Application Route: Ingestion

Exposure time: 28 dNumber of exposures: 7 d

Method: Subacute toxicity

Repeated dose toxicity - : No data available  
Assessment

### Aspiration toxicity

No data available

### Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

### Toxicology, Metabolism, Distribution

No data available

### Neurological effects

No data available

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

### Further information

Ingestion: No data available

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.5 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.7 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: Fresh water

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 9.4 mg/l  
Exposure time: 72 h  
Test Type: static test  
Test substance: Fresh water  
Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l  
Exposure time: 3 h  
Test Type: static test  
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.3 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: semi-static test  
Test substance: Fresh water  
Method: OECD Test Guideline 211

1,4-bis(2,3-epoxypropoxy)butane:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 24 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 75 mg/l  
Exposure time: 24 h  
Test Type: static test  
Test substance: Fresh water

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

Method: OECD Test Guideline 202

Toxicity to algae : EL50 : > 160 mg/l  
Exposure time: 72 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 201

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l  
Exposure time: 3 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 209

### 12.2 Persistence and degradability

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Inoculum: Sewage (STP effluent)  
Concentration: 20 mg/l  
Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4.83 d (25 °C)  
pH: 4  
Method: OECD Test Guideline 111  
Remarks: Fresh water

Degradation half life (DT50): 7.1 d (25 °C)  
pH: 9  
Method: OECD Test Guideline 111  
Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C)  
pH: 7  
Method: OECD Test Guideline 111  
Remarks: Fresh water

1,4-bis(2,3-epoxypropoxy)butane:

Biodegradability : Inoculum: activated sludge  
Concentration: 20 mg/l  
Result: Not readily biodegradable.  
Biodegradation: 43 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

### 12.3 Bioaccumulative potential

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 3.242 (25 °C)  
pH: 7.1  
Method: OECD Test Guideline 117

1,4-bis(2,3-epoxypropoxy)butane:  
Partition coefficient: n-octanol/water : log Pow: -0.269 (25 °C)  
pH: 6.7  
Method: OECD Test Guideline 117

### 12.4 Mobility in soil

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:  
Distribution among environmental compartments : Koc: 445

1,4-bis(2,3-epoxypropoxy)butane:  
Distribution among environmental compartments : Koc: 12.59  
Method: OECD Test Guideline 121

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
Dispose of as hazardous waste in compliance with local and national regulations.  
Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

Dispose of as unused product.  
Do not re-use empty containers.

### SECTION 14: Transport information

#### IATA

14.1 UN number	: UN 3082
14.2 UN proper shipping name	: Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A EPOXY RESIN)
14.3 Transport hazard class(es)	: 9
14.4 Packing group	: III
Labels	: Miscellaneous
Packing instruction (cargo aircraft)	: 964
Packing instruction (passenger aircraft)	: 964

#### IMDG

14.1 UN number	: UN 3082
14.2 UN proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)
14.3 Transport hazard class(es)	: 9
14.4 Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F
14.5 Environmental hazards	
Marine pollutant	: yes

#### ADR

14.1 UN number	: UN 3082
14.2 UN proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)
14.3 Transport hazard class(es)	: 9
14.4 Packing group	: III
Labels	: 9
14.5 Environmental hazards	
Environmentally hazardous	: yes

#### RID

14.1 UN number	: UN 3082
14.2 UN proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

**14.3 Transport hazard class(es)** : 9

**14.4 Packing group** : III

Labels : 9

**14.5 Environmental hazards**

Environmentally hazardous : yes

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regulation (EC) No

1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - List of substances subject to authorisation - Future sunset date : Not applicable

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

#### The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

TSCA : On the inventory, or in compliance with the inventory

### Inventories

AICS (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

### 15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

## SECTION 16: Other information

### Full text of H-Statements

H302	: Harmful if swallowed.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation

### Further information

#### Classification of the mixture:

Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 2	H411

#### Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.10.2018	400001008131	Date of first issue: 10.10.2018

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.